

# *Gloss measurement in pocket size* **for on the spot operations**

Very high accuracy and simple handling

Data transfer to PC via USB with the “My Gloss” application

Fully automatic calibration



# Mini **Gloss Tector 60°**

This instrument has been designed for fast, precise and easy gloss measurements of coatings, paints, synthetic materials, reflective surfaces and much more.



## One of the smallest gloss meters Mini **Gloss Tector 60°** in pocket size

### Specifications

Measurement Geometry:	60°
Size of Measurement Port:	10 x 20 mm (ellipse) (0.4 x 0.8 inches)
Size of Measurement Spot:	9 x 18 mm (0.35 x 0.7 inches)
Source of Illumination:	D65
Statistics:	Storage for 10 results
Interface:	USB
Software:	"My Gloss"
Battery:	1,5 V AAA (LR03)
Battery Capacity:	10.000 measurements respectively 60 hours
Size (L x W x H):	83 x 46 x 30 mm (3.27 x 1.81 x 1.18 inches)
Weight:	-100 g (without batteries) (0.22 lb)
Operating Temperature:	-10°C ~ 60°C (14°F ~ 140°F)
Relative Humidity:	85%
Measurement Range:	0 ~ 99,9 GE 100 ~ 1999 GE
Repetitive Accuracy:	± 0,2 GE (0 ~ 99,9 GE) 0,2% (100 ~ 1999 GE)
Measurement Accuracy:	± 0,5 GE (0 ~ 99,9 GE) 0,5% (100 ~ 1999 GE)

### Standard delivery range:

- Mini **Gloss Tector 60°**
- Holder with Gloss Standard
- Users Manual
- USB-Cable
- "My Gloss" Application
- Manufactures Inspection Certificate
- Hand Strap
- 2 Batteries 1.5 V (AAA)
- Service Case



### Characteristics:

- Very high accuracy
- Simple handling
- Fully automatic calibration
- Statistical Analysis
- Data transfer to PC via USB with the "My Gloss" application
- Battery operation

### Size:

- 83 x 46 x 30 mm (3.27 x 1.81 x 1.18 inches)
- Thus, the device is one of the smallest on the market.

### Application:

- Gloss measurement of colors and surfaces on automobile vehicles, electronic equipment or musical instruments
- Gloss measurement on floorboards, marble, granite and tiles in the architecture and decor industries
- Gloss measurement of ink and paper in the printing industry
- Gloss measurement of hard aluminum alloys
- Mainly used in the coating industry

Certified  
according to  
ISO EN 9001

MESSTECHNIK  
**SaluTron**<sup>®</sup>  
GmbH  
Herstellung und Vertrieb  
von Messgeräten

D-50226 Frechen · Dr.-Gottfried-Cremer-Allee 30/7  
Tel. +49 (0) 2234 99 99 96 0  
Fax. +49 (0) 2234 99 99 96 2  
info@salutron.de · www.salutron.de