

## TT-700



# TT-700 Coating thickness gauge



## Features

The new, ergonomically shaped handheld TT-700 Ultrasonic Wall thickness gauge offers big performance in a small light-weight package. Its biggest advantage is the measuring range from 0.15 up to 20mm (steel plates) which makes it suitable where other thickness gauges are out of range.

The operator keypad interface is user-friendly and has a central Mode key, a calibration key, three function arrow keys to activate and set functional control and navigate through the menu plus a key to store/transfer data. It has an integrated steel calibration plate and the display resolution can be switched from 0.001 to 0.01mm. If you need to document your measuring results, they can be printed or transferred to a PC.

- Especially suitable for testing thin workpieces
- I-E testing mode and E-E testing mode
- Sound velocity testing and single point calibration
- Sound alarm and differential mode are available
- Mm/inch selectable
- Data store, view and delete
- Results can be print out and transfer to PC

## Technical specifications

|                       |  |
|-----------------------|--|
| Measuring range       | 0.15mm ~ 20mm (1mm $\phi$ 5mm steel pipes) |
| Display resolution    | 0.001mm and 0.01mm selectable              |
| Sound velocity range  | 1000m/s ~ 9999m/s                          |
| Operating temperature | 0~40°C                                     |
| Dimensions            | 152mm x 74mm x 35mm                        |
| Weight                | 220gr                                      |
| Power supply          | 2pcs AA batteries                          |

## Standard delivery

- Instrument
- Transducer 15P $\phi$ 6
- Screw driver
- Protection cover
- AA battery (2 pcs)
- Couplant
- Manual
- INNOVATEST® certificate
- Carrying case



## Optional accessories

- Communication cable
- Standard test block
- 20MHz transducer
- TA-230 printer

## Order details

**TT-700** Coating wall thickness gauge with external transducer especially suitable for thin workpieces

Represented by:

SaluTron Messtechnik GmbH  
Dr.-Gottfried-Cremer-Allee 30/7  
D-50226 Frechen

IN09-039 170215

## CORPORATE HEAD OFFICE

### **INNOVATEST Europe BV** **MANUFACTURING, DISTRIBUTION & SERVICE**

Borgharenweg 140  
6222 AA Maastricht (The Netherlands)  
Phone: +31 43 3520060  
Fax: +31 43 3631168  
E-mail: [info@innovatest-europe.com](mailto:info@innovatest-europe.com)  
Website: [www.innovatest-europe.com](http://www.innovatest-europe.com)

---

## BRANCHE OFFICES

### **INNOVATEST Benelux BVBA** **SALES & SERVICE**

Phone: +32 12 779002  
Fax: +32 12 779003  
E-mail: [info@innovatest-benelux.com](mailto:info@innovatest-benelux.com)  
Website: [www.innovatest-europe.com](http://www.innovatest-europe.com)

### **INNOVATEST Shanghai Co., Ltd.** **ASIA & CHINA SALES & SERVICE**

Building 2, No.123, 1165 Nong Jindu Road,  
South Metropolis Industrial Park  
Minhang District, Shanghai, P.R. China  
Zip code: 201108  
E-mail: [info@innovatest-shanghai.com](mailto:info@innovatest-shanghai.com)  
Website: [www.innovatest-shanghai.com](http://www.innovatest-shanghai.com)

Changes in products and/or product specifications can emerge due to new technologies and continuous development.

We reserve the right to change or modify specifications of products without prior notice.

We recommend you to contact our sales office for up-to-date information.

© All rights reserved